

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : arecal Galva Zinc Premium zinc spray 400 ml

Product code : 0897 114 400

Unique Formula Identifier (UFI) : SC00-60HP-E00Y-GV09

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Industrial paint
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : RECA FRANCE
5, rue Edouard Branly
67116 Reichstett

Telephone : +33 03 90 20 35 50

E-mail address of person responsible for the SDS : sds@reca.com

1.4 Emergency telephone number

ORFILA (France) +33 (0) 1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Aerosols, Category 1 | H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Specific target organ toxicity - single exposure, Category 3 | H336: May cause drowsiness or dizziness. |
| Long-term (chronic) aquatic hazard, Cat- | H411: Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Dimethyl ether
Acetone
Solvent naphtha (petroleum), light arom.
Naphtha (petroleum), hydrotreated heavy

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| Dimethyl ether | 115-10-6 204-065-8 603-019-00-8 | Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336 | >= 50 - < 70 |
| Acetone | 67-64-1 200-662-2 606-001-00-8 | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066 | >= 10 - < 20 |
| Xylene | 1330-20-7 215-535-7 601-022-00-9 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg | >= 2,5 - < 10 |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 265-199-0 649-356-00-4 | Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 | >= 2,5 - < 10 |
| Ethylbenzene | 100-41-4 202-849-4 601-023-00-4 | Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 | >= 2,5 - < 10 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

| | | | |
|---|---|--|-------------------|
| | | (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | |
| | | Acute toxicity estimate | |
| | | Acute inhalation toxicity (vapour): 17,8 mg/l | |
| Zinc | 7440-66-6 231-175-3 030-001-01-9 | Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | $\geq 2,5 - < 10$ |
| | | M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 265-150-3 649-327-00-6 | Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066 | $\geq 1 - < 10$ |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

- Advice on safe handling : Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
- Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases
- Recommended storage temperature : < 40 °C

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--|--|-------------------------------|--------------------------------------|------------|
| Dimethyl ether | 115-10-6 | TWA | 1.000 ppm 1.920 mg/m ³ | 2000/39/EC |
| | Further information: Indicative | | | |
| | | VME | 1.000 ppm 1.920 mg/m ³ | FR VLE |
| | Further information: Regulatory indicative exposure limits | | | |
| Acetone | 67-64-1 | TWA | 500 ppm 1.210 mg/m ³ | 2000/39/EC |
| | Further information: Indicative | | | |
| | | VLCT (VLE) | 1.000 ppm 2.420 mg/m ³ | FR VLE |
| | Further information: Regulatory binding exposure limits | | | |
| | | VME | 500 ppm 1.210 mg/m ³ | FR VLE |
| | Further information: Regulatory binding exposure limits | | | |
| Xylene | 1330-20-7 | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | VME | 50 ppm 221 mg/m ³ | FR VLE |
| | Further information: Risk of penetration through skin, Regulatory binding exposure limits | | | |
| | | VLCT (VLE) | 100 ppm 442 mg/m ³ | FR VLE |
| | Further information: Risk of penetration through skin, Regulatory binding exposure limits | | | |
| Solvent naphtha (petroleum), light arom. | 64742-95-6 | VME (Vapour) | 150 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |
| Ethylbenzene | 100-41-4 | TWA | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | STEL | 200 ppm 884 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | VME | 20 ppm 88,4 mg/m ³ | FR VLE |
| | Further information: Risk of penetration through skin, Regulatory binding exposure limits | | | |
| | | VLCT (VLE) | 100 ppm 442 mg/m ³ | FR VLE |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

| | | | | |
|---|---|---------------------|-------------------------|--------|
| | Further information: Risk of penetration through skin, Regulatory binding exposure limits | | | |
| Aluminium | 7429-90-5 | VME | 10 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |
| | | VME (powder) | 5 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |
| | | VME (Welding fumes) | 5 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | VME (Vapour) | 1.000 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |
| | | VLCT (VLE) (Vapour) | 1.500 mg/m ³ | FR VLE |
| | Further information: Permissible limit values (circular) | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|----------------|-----------------|----------------------------|----------------------------|
| Ethylbenzene | Workers | Inhalation | Long-term systemic effects | 77 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 293 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 180 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 15 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 1,6 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 221 mg/m ³ |
| Xylene | Workers | Inhalation | Long-term systemic effects | 221 mg/m ³ |
| | Workers | Inhalation | Acute systemic effects | 442 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 221 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 442 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 212 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 65,3 mg/m ³ |
| | Consumers | Inhalation | Acute systemic effects | 260 mg/m ³ |
| | Consumers | Inhalation | Long-term local effects | 65,3 mg/m ³ |
| | Consumers | Inhalation | Acute local effects | 260 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 125 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 12,5 mg/kg bw/day |
| | Dimethyl ether | Workers | Inhalation | Long-term systemic effects |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

| | | | | |
|---|-----------|--------------|----------------------------|------------------------|
| | Consumers | Inhalation | Long-term systemic effects | 471 mg/m ³ |
| Zinc | Workers | Inhalation | Long-term systemic effects | 5 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 83 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 2,5 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 83 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 0,83 mg/kg bw/day |
| Acetone | Workers | Inhalation | Long-term systemic effects | 1210 mg/m ³ |
| | Workers | Inhalation | Acute local effects | 2420 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 186 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 200 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 62 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 62 mg/kg bw/day |
| Aluminium | Workers | Inhalation | Long-term local effects | 3,72 mg/m ³ |
| | Consumers | Ingestion | Long-term systemic effects | 3,95 mg/kg bw/day |
| Naphtha (petroleum), hydrotreated heavy | Workers | Inhalation | Long-term systemic effects | 871 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 77 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 185 mg/m ³ |
| | Consumers | Skin contact | Long-term systemic effects | 46 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 46 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|----------------|----------------------------|------------------------------|
| Ethylbenzene | Fresh water | 0,1 mg/l |
| | Freshwater - intermittent | 0,1 mg/l |
| | Marine water | 0,01 mg/l |
| | Sewage treatment plant | 9,6 mg/l |
| | Fresh water sediment | 13,7 mg/kg dry weight (d.w.) |
| | Marine sediment | 1,37 mg/kg dry weight (d.w.) |
| | Soil | 2,68 mg/kg dry weight (d.w.) |
| Xylene | Oral (Secondary Poisoning) | 20 mg/kg food |
| | Fresh water | 0,327 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

| | | |
|----------------|--------------------------|-------------------------------|
| | Intermittent use/release | 0,327 mg/l |
| | Marine water | 0,327 mg/l |
| | Sewage treatment plant | 6,58 mg/l |
| | Fresh water sediment | 12,46 mg/kg dry weight (d.w.) |
| | Marine sediment | 12,46 mg/kg dry weight (d.w.) |
| | Soil | 2,31 mg/kg dry weight (d.w.) |
| Dimethyl ether | Fresh water | 0,155 mg/l |
| | Marine water | 0,016 mg/l |
| | Intermittent use/release | 1,549 mg/l |
| | Sewage treatment plant | 160 mg/l |
| | Fresh water sediment | 0,681 mg/kg dry weight (d.w.) |
| | Marine sediment | 0,069 mg/kg dry weight (d.w.) |
| | Soil | 0,045 mg/kg dry weight (d.w.) |
| Zinc | Fresh water | 20,6 µg/l |
| | Marine water | 6,1 µg/l |
| | Sewage treatment plant | 100 µg/l |
| | Fresh water sediment | 117,8 mg/kg |
| | Marine sediment | 56,5 mg/kg |
| | Soil | 35,6 mg/kg |
| Acetone | Fresh water | 10,6 mg/l |
| | Marine water | 1,06 mg/l |
| | Intermittent use/release | 21 mg/l |
| | Sewage treatment plant | 100 mg/l |
| | Fresh water sediment | 30,4 mg/kg dry weight (d.w.) |
| | Marine sediment | 3,04 mg/kg dry weight (d.w.) |
| | Soil | 29,5 mg/kg dry weight (d.w.) |
| Aluminium | Sewage treatment plant | 20 mg/l |

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to NF EN 166

Hand protection

Material : Nitrile rubber

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Break through time : > 480 min
Glove thickness : > 0,4 mm
Directive : Equipment should conform to NF EN 374

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : > 0,4 mm
Directive : Equipment should conform to NF EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to NF EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Dimethyl ether

Colour : silver, grey

Odour : characteristic

Odour Threshold : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 13,8 %(V)

Lower explosion limit / Lower flammability limit : 1,2 %(V)

Flash point : Not applicable

Auto-ignition temperature : 470 °C
Method: DIN 51794

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Viscosity
Viscosity, kinematic : Not applicable

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : 3,2 hPa (20 °C)

Density : 0,784 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics
Particle size : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

Acetone:

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 (Rat, female): 3.492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Zinc:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Solvent naphtha (petroleum), light arom.:

Assessment : Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit
Result : Mild skin irritation
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Acetone:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Solvent naphtha (petroleum), light arom.:

Species : Rabbit
Result : No eye irritation

Zinc:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Acetone:

Test Type : Maximisation Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Solvent naphtha (petroleum), light arom.:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Naphtha (petroleum), hydrotreated heavy:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Solvent naphtha (petroleum), light arom.:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Zinc:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Naphtha (petroleum), hydrotreated heavy:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: inhalation (vapour)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Solvent naphtha (petroleum), light arom.:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Ethylbenzene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Naphtha (petroleum), hydrotreated heavy:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Components:

Dimethyl ether:

- Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Acetone:

- Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Xylene:

- Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Solvent naphtha (petroleum), light arom.:

- Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: inhalation (vapour)
Result: negative

Ethylbenzene:

- Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Naphtha (petroleum), hydrotreated heavy:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Acetone:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Solvent naphtha (petroleum), light arom.:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

Naphtha (petroleum), hydrotreated heavy:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47,11 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1.700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapour)
Exposure time : 8 Weeks

Xylene:

Species : Rat
LOAEL : > 0,2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Solvent naphtha (petroleum), light arom.:

Species : Rat, female

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

NOAEL : 900 mg/m³
Application Route : inhalation (vapour)
Exposure time : 12 Months
Remarks : Based on data from similar materials

Ethylbenzene:

Species : Rat
LOAEL : 0,868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

Zinc:

Species : Rat
NOAEL : 31 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Naphtha (petroleum), hydrotreated heavy:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 500 mg/kg
Application Route : Skin contact
Exposure time : 28 Days

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light arom.:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Naphtha (petroleum), hydrotreated heavy:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l
Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8.800 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 : 61.150 mg/l
Exposure time: 30 min
Method: ISO 8192

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 79 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,2 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

Version 5.0 Revision Date: 04.11.2024 SDS Number: 8077880-00007 Date of last issue: 03.06.2024
Date of first issue: 01.04.2021

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 7,9 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,22 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 99 mg/l
Exposure time: 10 min

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

Zinc:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0,78 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,83 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (Pseudokirchneriella subcapitata (green algae)): 0,15 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 : 5,2 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,199 mg/l
Exposure time: 30 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

Naphtha (petroleum), hydrotreated heavy:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Method: OECD Test Guideline 301D

Acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Solvent naphtha (petroleum), light arom.:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Naphtha (petroleum), hydrotreated heavy:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0,2

Acetone:

Partition coefficient: n-octanol/water : log Pow: -0,27 - -0,23

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3,16
Remarks: Calculation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Solvent naphtha (petroleum), light arom.:

Partition coefficient: n-octanol/water : log Pow: 3,7 - 4,5

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3,6

Zinc:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 177

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or ex-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

pose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code

: The following Waste Codes are only suggestions:

unused product

16 05 04*, gases in pressure containers (including halons) containing hazardous substances

used product

16 05 04*, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings

15 01 10*, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

| | | |
|------|---|---------|
| ADN | : | UN 1950 |
| ADR | : | UN 1950 |
| RID | : | UN 1950 |
| IMDG | : | UN 1950 |
| IATA | : | UN 1950 |

14.2 UN proper shipping name

| | | |
|------|---|--|
| ADN | : | AEROSOLS |
| ADR | : | AEROSOLS |
| RID | : | AEROSOLS |
| IMDG | : | AEROSOLS (Zinc, Solvent naphtha (petroleum), light arom.) |
| IATA | : | Aerosols, flammable |

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 2 | 2.1 |
| ADR | : 2 | 2.1 |
| RID | : 2 | 2.1 |
| IMDG | : 2.1 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Acetone (ANNEX II)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

| | | Quantity 1 | Quantity 2 |
|-----|-----------------------|------------|------------|
| P3a | FLAMMABLE AEROSOLS | 150 t | 500 t |
| E2 | ENVIRONMENTAL HAZARDS | 200 t | 500 t |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

| | | | |
|----|--|---------|----------|
| 34 | Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) | 2.500 t | 25.000 t |
|----|--|---------|----------|

Occupational Illnesses (R-461-3, France) : 84, 43, 43bis, 4 bis, 36

Reinforced medical supervision (R4624-23) : The product has no CMR properties category 1, 1A or 1B

Installations classified for the protection of the environment (Environment Code R511-9) : 4320, 4511, 4734

Volatile organic compounds : Directive 2004/42/EC
VOC content in g/l: 677,1 g/l
Product sub-category: Special finishes
Coatings: All types
VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 85,95 %, 677,1 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
FR VLE : France. Occupational Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
FR VLE / VME : Time Weighted Average
FR VLE / VLCT (VLE) : Short Term Exposure Limit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

| | |
|-------------------|------------|
| Aerosol 1 | H222, H229 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal Galva Zinc Premium zinc spray 400 ml

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03.06.2024 |
| 5.0 | 04.11.2024 | 8077880-00007 | Date of first issue: 01.04.2021 |

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

FR / EN