

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : arecal dry lubricant spray

Product code : 0896 712 400

Unique Formula Identifier (UFI) : N2Q0-8053-X006-U7EM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricant, Corrosion inhibitor
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : RECA NORM GmbH
Am Wasserturm 4
DE-74635 Kupferzell

Telephone : +49 7944 61 0

E-mail address of person responsible for the SDS : sds@reca.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878





arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H222	Extremely flammable aerosol.
		H229	Pressurised container: May burst if heated.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H336	May cause drowsiness or dizziness.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P211	Do not spray on an open flame or other ignition source.
		P251	Do not pierce or burn, even after use.
		P273	Avoid release to the environment.
		P280	Wear protective gloves.
		Storage:	
		P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, isoalkanes
Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7-C9, isoalkanes	64741-66-8 265-068-8 649-276-00-X 01-2119471305-42	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
Dec-1-ene, homopolymer, hydrogenated	68037-01-4 01-2119486452-34	Asp. Tox. 1; H304	>= 1 - < 10
Disodium sebacate	17265-14-4 241-300-3	Eye Irrit. 2; H319	>= 1 - < 10
Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts	97675-24-6 307-593-8 01-2119985174-30	Skin Sens. 1B; H317	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

Hygiene measures : Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases

Storage class (TRGS 510) : 2B

Recommended storage temperature : < 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 4;(II)		
		MAK	1.000 ppm 2.400 mg/m ³	DE DFG MAK
		Peak-limit: excursion factor (category): 4; II		
		Further information: Either there are no data for an assessment of damage to		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

		the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C		
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 2.400 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 1.800 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Dec-1-ene, homo-polymer, hydro-genated	68037-01-4	AGW (Alveolate fraction)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (measured as the alveolate fraction)	5 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Dec-1-ene, homo-polymer, hydro-genated	68037-01-4	AGW (Alveolate fraction)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (measured as the alveolate fraction)	5 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term systemic effects	6,36 mg/m ³
	Consumers	Ingestion	Acute systemic ef-	6,1 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

			fects	bw/day
	Consumers	Inhalation	Long-term systemic effects	1,06 mg/m3
	Consumers	Ingestion	Long-term systemic effects	6,1 mg/kg bw/day
Disodium sebacate	Workers	Inhalation	Long-term systemic effects	35,26 mg/m3
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m3
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts	Workers	Inhalation	Long-term systemic effects	0,66 mg/m3
	Workers	Skin contact	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,33 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,667 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,833 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
Disodium sebacate	Fresh water	0,018 mg/l
	Intermittent use/release	0,18 mg/l
	Marine water	0,002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,548 mg/kg dry weight (d.w.)
	Marine sediment	0,055 mg/kg dry weight (d.w.)
	Soil	0,099 mg/kg dry weight (d.w.)
Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts	Fresh water	1 mg/l
	Marine water	1 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	723500000 mg/kg dry weight (d.w.)
	Marine sediment	723500000 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

	Soil	868700000 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	16,667 mg/kg food

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,45 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Butane, Isobutane, Propane

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Colour	:	white
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	15 %(V)
Lower explosion limit / Lower flammability limit	:	1,5 %(V)
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, kinematic	:	< 20,5 mm ² /s (40 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	Not applicable
Density	:	0,8 g/cm ³ (20 °C) Method: DIN 51757
Relative vapour density	:	Not applicable
Particle characteristics	:	
Particle size	:	Not applicable

9.2 Other information

Explosives	:	Not explosive
------------	---	---------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 9,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Acute dermal toxicity : LD50 (Rabbit): > 2.200 - 2.500 mg/kg
Remarks: Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1,9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Result : No skin irritation

Disodium sebacate:

Species : Rabbit
Result : No skin irritation

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Disodium sebacate:

Species : Bovine cornea
Method : OECD Test Guideline 437

Species : Tissue Culture
Method : EpiOcular

Result : Irritation to eyes, reversing within 21 days

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Disodium sebacate:

Test Type : Intracutaneous test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Disodium sebacate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal develop- : Test Type: Embryo-foetal development

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

NOAEL : 4.159,4 mg/kg
Application Route : Ingestion
Exposure time : 91 Days

Disodium sebacate:

Species : Rat
NOAEL : ≥ 1.000 mg/kg
Application Route : Ingestion
Exposure time : 6 Months

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Species : Rat
NOAEL : 1.000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, isoalkanes:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Dec-1-ene, homopolymer, hydrogenated:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

Components:

Hydrocarbons, C7-C9, isoalkanes:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 18,4 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 2,4 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOELR (Pseudokirchneriella subcapitata (green algae)): 6,3 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Scenedesmus capricornutum (fresh water algae)): > 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Scenedesmus capricornutum (fresh water algae)): 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : 2 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 301D

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 125 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211

Disodium sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Acartia tonsa (Calanoid copepod)): > 10 - 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: ISO 14669 and PARCOM method
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOELR (Skeletonema costatum (marine diatom)): > 1 - 10 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253
Remarks: Based on data from similar materials

EL50 (Skeletonema costatum (marine diatom)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253
Remarks: Based on data from similar materials

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): > 1.000 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Test substance: Water Accommodated Fraction

NOELR (Pseudokirchneriella subcapitata (algae)): 1.000 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

12.2 Persistence and degradability

Components:

Hydrocarbons, C7-C9, isoalkanes:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 61,81 %
Exposure time: 70 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Dec-1-ene, homopolymer, hydrogenated:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Disodium sebacate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 306

Benzene, C9-13-alkyl derivs., distn. residues, sulfonated, calcium salts:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

Dec-1-ene, homopolymer, hydrogenated:

Partition coefficient: n- : log Pow: > 6,5
octanol/water

Disodium sebacate:

Partition coefficient: n- : log Pow: -4,9
octanol/water

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	: Please ensure aerosol cans are sprayed completely empty (including propellant) Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.
Waste Code	: The following Waste Codes are only suggestions: used product 16 05 04*, gases in pressure containers (including halons) containing hazardous substances 13 02 06, synthetic engine, gear and lubricating oils unused product 16 05 04*, gases in pressure containers (including halons) containing hazardous substances 13 02 06, synthetic engine, gear and lubricating oils uncleaned packagings

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024



15 01 10*, packaging containing residues of or contaminated
by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version 2.0 Revision Date: 11.10.2024 SDS Number: 11391779-00002 Date of last issue: 23.05.2024
Date of first issue: 23.05.2024

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable
Regulation (EC) on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Class 1: < 0,01 % Diphenylamine
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 90,11 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national
regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version
are highlighted in the body of this document by two vertical
lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

STOT SE	:	Specific target organ toxicity - single exposure
DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



arecal dry lubricant spray

Version	Revision Date:	SDS Number:	Date of last issue: 23.05.2024
2.0	11.10.2024	11391779-00002	Date of first issue: 23.05.2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN