

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : arecal Rust stop primer red/brown 400 ml

Product code : 0897 261 400

Unique Formula Identifier (UFI) : HQ60-N0M2-300M-E442

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings, Paint, Special finishes  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : RECA HISPANIA SAU  
Ciudad de Liria N° 21  
46988 Fuente del Jaro/Paterna

Telephone : +34 96 15194 60

E-mail address of person responsible for the SDS : sds@reca.com

#### 1.4 Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses  
+ 34 (0)91 562 04 20

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P273 Avoid release to the environment.

#### **Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### **Hazardous components which must be listed on the label:**

Acetone  
n-Butyl acetate  
2-Methoxy-1-methylethyl acetate

#### **Additional Labelling**

EUH208 Contains Maleic anhydride, 4-Morpholinecarbaldehyde. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 10 - < 20
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 3; H412  Acute toxicity estimate  Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 1 - < 2,5
Trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319  specific concentration limit Eye Irrit. 2; H319 >= 50 %	>= 1 - < 10
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10
Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	>= 1 - < 10
4-Morpholinecarbaldehyde	4394-85-8 224-518-3 01-2119987993-12	Skin Sens. 1B; H317	>= 0,1 - < 1
Maleic anhydride	108-31-6 203-571-6 607-096-00-9	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory Tract) EUH071  specific concentration limit Skin Sens. 1A; H317 >= 0,001 %  Acute toxicity estimate  Acute oral toxicity: 1.090 mg/kg	< 0,001

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.
- May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Metal oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate contain-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |   |
|-------------------------|---|---|
| Technical measures      | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.   |
| Advice on safe handling | : | Do not get on skin or clothing.<br>Avoid breathing spray.<br>Do not swallow.<br>Do not get in eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br>Do not spray on an open flame or other ignition source. |
| Hygiene measures        | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.  |

### 7.2 Conditions for safe storage, including any incompatibilities

- |   |   |  |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
|---|---|--|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Recommended storage temperature : < 40 °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
		Further information: Indicative		
		VLA-ED	500 ppm 1.210 mg/m <sup>3</sup>	ES VLA
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
		Further information: Indicative		
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
		Further information: Indicative		
		VLA-ED	50 ppm 241 mg/m <sup>3</sup>	ES VLA
		VLA-EC	150 ppm 723 mg/m <sup>3</sup>	ES VLA
Propane	74-98-6	VLA-ED (gas)	1.000 ppm	ES VLA
Butane	106-97-8	VLA-ED (gas)	1.000 ppm	ES VLA
Isobutane	75-28-5	VLA-ED (gas)	1.000 ppm	ES VLA
Xylene	1330-20-7	VLA-ED	50 ppm 221 mg/m <sup>3</sup>	ES VLA
		Further information: Skin		
		VLA-EC	100 ppm 442 mg/m <sup>3</sup>	ES VLA



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

	Further information: Skin			
		TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
Talc	14807-96-6	VLA-ED (respirable fraction)	2 mg/m <sup>3</sup>	ES VLA
Ethanol	64-17-5	VLA-EC	1.000 ppm 1.910 mg/m <sup>3</sup>	ES VLA
2-Methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-ED	50 ppm 275 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
		VLA-EC	100 ppm 550 mg/m <sup>3</sup>	ES VLA
	Further information: Skin			
Diiron trioxide	1309-37-1	VLA-ED (dust and fume)	5 mg/m <sup>3</sup> (Iron)	ES VLA
Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	VLA-ED	10 mg/m <sup>3</sup>	ES VLA
Maleic anhydride	108-31-6	VLA-ED (Inhalable fraction and vapor)	0,1 ppm 0,4 mg/m <sup>3</sup>	ES VLA
	Further information: Sensitizer agent			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Acetone	67-64-1	Acetone: 50 mg/l (Urine)	End of workday	ES VLB
Xylene	1330-20-7	methylhippuric acids: 1 g/g creatinine (Urine)	End of workday	ES VLB

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day
	Consumers	Ingestion	Acute local effects	500 mg/kg bw/day
Maleic anhydride	Workers	Inhalation	Long-term systemic effects	0,4 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	0,8 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	0,4 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	0,8 mg/m <sup>3</sup>
Ethanol	Workers	Inhalation	Long-term systemic effects	380 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	267 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m <sup>3</sup>
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
4-Morpholinecarbaldehyde	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	14 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0,293 mg/cm <sup>2</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

	Consumers	Inhalation	Long-term systemic effects	29 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0,176 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	8 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
Acetone	Soil	0,09 mg/kg dry weight (d.w.)
	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
Trizinc bis(orthophosphate)	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Marine sediment	3,04 mg/kg dry weight (d.w.)
	Soil	29,5 mg/kg dry weight (d.w.)
	Fresh water	20,6 µg/l
	Marine water	6,1 µg/l
2-Methoxy-1-methylethyl acetate	Sewage treatment plant	100 µg/l
	Fresh water sediment	117,8 mg/kg
	Marine sediment	56,5 mg/kg
	Soil	35,6 mg/kg
	Fresh water	0,635 mg/l
Maleic anhydride	Freshwater - intermittent	6,35 mg/l
	Marine water	0,0635 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Freshwater - intermittent	0,4281 mg/l
	Sewage treatment plant	44,6 mg/l
	Fresh water sediment	0,334 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

	Marine sediment	0,0334 mg/kg dry weight (d.w.)
	Soil	0,0415 mg/kg dry weight (d.w.)
Ethanol	Fresh water	0,96 mg/l
	Freshwater - intermittent	2,75 mg/l
	Marine water	0,79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Soil	0,63 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food
Xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
4-Morpholinecarbaldehyde	Fresh water	0,5 mg/l
	Marine water	0,05 mg/l
	Sewage treatment plant	2000 mg/l
	Fresh water sediment	2,69 mg/kg dry weight (d.w.)
	Marine sediment	0,269 mg/kg dry weight (d.w.)
	Soil	0,244 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles  
Equipment should conform to UNE EN 166

Hand protection

Material : butyl-rubber  
Break through time : < 480 min  
Glove thickness : 0,4 mm

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

- Directive : Equipment should conform to UNE EN 374
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to UNE EN 137
- Filter type : Self-contained breathing apparatus
- 

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : Aerosol containing a liquefied gas
- Propellant : Propane, Butane, Isobutane
- Colour : red brown
- Odour : characteristic
- Odour Threshold : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 13 %(V)

Lower explosion limit / Lower flammability limit : 1,2 %(V)

Flash point : Not applicable

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)  
Water solubility : immiscible

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : 8.300 hPa (20 °C)

Density : 0,8 g/cm<sup>3</sup> (20 °C)

Relative vapour density : Not applicable

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### **Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

---



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

### Components:

#### **Acetone:**

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

#### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

#### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

#### **Trizinc bis(orthophosphate):**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Remarks: Based on data from similar materials

#### **Ethanol:**

Acute oral toxicity : LD50 (Rat): 10.470 mg/kg  
Method: OECD Test Guideline 401

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Acute inhalation toxicity : LC50 (Rat, male): 116,9 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 15.800 mg/kg

### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat, female): 5.155 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 9,34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

### **4-Morpholinecarbaldehyde:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): >= 5,319 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

### **Maleic anhydride:**

Acute oral toxicity : LD50 (Rat): 1.090 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 4,35 mg/l  
Exposure time: 1 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 2.620 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

---

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

#### **Components:**

##### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

##### **n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

##### **Xylene:**

Species : Rabbit  
Result : Skin irritation

##### **Trizinc bis(orthophosphate):**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

##### **Ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No skin irritation

##### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rabbit  
Result : No skin irritation

##### **4-Morpholinecarbaldehyde:**

Species : Rabbit  
Result : No skin irritation

##### **Maleic anhydride:**

Species : in vitro membrane barrier  
Method : OECD Test Guideline 435  
Remarks : Based on data from similar materials

Result : Corrosive after 3 minutes to 1 hour of exposure

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

---

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Components:**

##### **Acetone:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

##### **n-Butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

##### **Xylene:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

##### **Trizinc bis(orthophosphate):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

##### **Ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

##### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No eye irritation

##### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rabbit  
Result : No eye irritation

##### **4-Morpholinecarbaldehyde:**

Species : Rabbit  
Result : No eye irritation

##### **Maleic anhydride:**

Species : Rabbit  
Result : Irreversible effects on the eye

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

---

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Acetone:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

##### n-Butyl acetate:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

##### Xylene:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

##### Trizinc bis(orthophosphate):

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

Assessment : Does not cause skin sensitisation.

##### Ethanol:

Test Type : Mouse ear swelling test (MEST)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

##### 2-Methoxy-1-methylethyl acetate:

Test Type : Maximisation Test  
Exposure routes : Skin contact

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

### **4-Morpholinecarbaldehyde:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

### **Maleic anhydride:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

Exposure routes : inhalation (dust/mist/fume)  
Species : Rat  
Result : positive

Assessment : Probability of respiratory sensitisation in humans based on animal testing

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

### **Xylene:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

### **Trizinc bis(orthophosphate):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

### **Ethanol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Species: Rat  
Application Route: Ingestion  
Result: negative

### 2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

### 4-Morpholinecarbaldehyde:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

### Maleic anhydride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### Carcinogenicity

Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

### Components:

#### **Acetone:**

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	424 days
Result	:	negative

#### **Xylene:**

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

#### **2-Methoxy-1-methylethyl acetate:**

Species	:	Rat
Application Route	:	inhalation (vapour)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453
Result	:	negative
Remarks	:	Based on data from similar materials

#### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species	:	Rat
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453
Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment	:	Limited evidence of carcinogenicity in inhalation studies with animals.
------------------------------	---	---

#### **Maleic anhydride:**

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	2 Years
Result	:	negative

#### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Acetone:**

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion
----------------------	---	---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Trizinc bis(orthophosphate):**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### **Ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **4-Morpholinecarbaldehyde:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 421  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### **Maleic anhydride:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Acetone:**

Assessment : May cause drowsiness or dizziness.

#### **n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Xylene:**

Assessment : May cause respiratory irritation.

#### **2-Methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

### STOT - repeated exposure

Not classified based on available information.

#### Components:

##### Maleic anhydride:

Exposure routes	: inhalation (vapour)
Target Organs	: Respiratory Tract
Assessment	: Shown to produce significant health effects in animals at concentrations of 0.2 mg/l/6h/d or less.

### Repeated dose toxicity

#### Components:

##### Acetone:

Species	: Rat
NOAEL	: 900 mg/kg
LOAEL	: 1.700 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Species	: Rat
NOAEL	: 45 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 8 Weeks

##### n-Butyl acetate:

Species	: Rat
NOAEL	: 2,4 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 90 Days

##### Xylene:

Species	: Rat
LOAEL	: 150 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

##### Trizinc bis(orthophosphate):

Species	: Rat
NOAEL	: 31,52 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks
Method	: OECD Test Guideline 408
Remarks	: Based on data from similar materials

##### Ethanol:

Species	: Rat
NOAEL	: 1.730 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

LOAEL : 3.200 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### 2-Methoxy-1-methylethyl acetate:

Species : Rat  
NOAEL :  $\geq 1.000$  mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Rat  
NOAEL :  $> 1$  mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr  
Method : OECD Test Guideline 453  
Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL :  $> 200$  mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:

Species : Rat  
NOAEL : 24.000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days

Species : Rat  
NOAEL : 10 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 yr

### 4-Morpholinecarbaldehyde:

Species : Rat  
NOAEL : 1.000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 d  
Method : OECD Test Guideline 407

### Maleic anhydride:

Species : Rat  
LOAEL : 100 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Species	:	Rat
LOAEL	:	0,01 mg/l
Application Route	:	inhalation (vapour)
Exposure time	:	28 Days

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### Acetone:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8.800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000 mg/l Exposure time: 96 h
Toxicity to microorganisms	:	EC50 : 61.150 mg/l Exposure time: 30 min Method: ISO 8192

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC:  $\geq 79$  mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **n-Butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23,2 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)):  $> 1 - 10$  mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : NOEC :  $> 100$  mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox- : NOEC:  $> 0,1 - < 1$  mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

icity) Exposure time: 35 d  
Species: Danio rerio (zebra fish)  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Trizinc bis(orthophosphate):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 169 µg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 155 µg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 24 µg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 39 µg/l  
Exposure time: 30 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 95 µg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

### Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 14.200 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 5.012 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

plants Exposure time: 72 h  
EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Protozoa): 5.800 mg/l  
Exposure time: 4 h

Toxicity to fish (Chronic toxicity) : NOEC:  $\geq$  79 mg/l  
Exposure time: 100 d  
Species: Oryzias latipes (Japanese medaka)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9,6 mg/l  
Exposure time: 9 d  
Species: Daphnia magna (Water flea)

### 2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): > 1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)):  $\geq$  1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (activated sludge): > 1.000 mg/l  
Exposure time: 30 min

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC:  $\geq$  100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

aquatic invertebrates : Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10.000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 : > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### 4-Morpholinecarbaldehyde:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l  
Exposure time: 96 h  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 2.000 mg/l  
Exposure time: 17 h  
Method: DIN 38 412 Part 8

### Maleic anhydride:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 115 mg/l  
Exposure time: 48 h  
Test substance: Neutralised product  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h  
Test substance: Neutralised product  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (microalgae)): > 150 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 44,6 mg/l  
Exposure time: 18 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Test substance: Neutralised product  
Method: DIN 38 412 Part 8

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### 12.2 Persistence and degradability

#### Components:

##### **Acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

##### **n-Butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 84 %  
Exposure time: 20 d

##### **2-Methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **4-Morpholinecarbaldehyde:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301A

##### **Maleic anhydride:**

Biodegradability : Result: Readily biodegradable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Biodegradation: 93,2 %  
Exposure time: 11 d  
Method: OECD Test Guideline 301B

### 12.3 Bioaccumulative potential

#### Components:

##### **Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0,27 - -0,23

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3

##### **Xylene:**

Partition coefficient: n-octanol/water : log Pow: 3,16  
Remarks: Calculation

##### **Ethanol:**

Partition coefficient: n-octanol/water : log Pow: -0,35

##### **2-Methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2

##### **4-Morpholinecarbaldehyde:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): < 1,9  
Method: OECD Test Guideline 305C

Partition coefficient: n-octanol/water : log Pow: -1,2

##### **Maleic anhydride:**

Partition coefficient: n-octanol/water : log Pow: -2,61

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)
Waste Code	: The following Waste Codes are only suggestions:  used product 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances  unused product 08 01 11*, waste paint and varnish containing organic solvents or other hazardous substances  uncleaned packagings 15 01 10*, packaging containing residues of or contaminated by hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

#### 14.2 UN proper shipping name

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.1
<b>ADR</b>	: 2	2.1
<b>RID</b>	: 2	2.1
<b>IMDG</b>	: 2.1	
<b>IATA</b>	: 2.1	

#### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) :

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version 4.0      Revision Date: 08.11.2024      SDS Number: 9161531-00007      Date of last issue: 25.06.2024  
Date of first issue: 05.08.2021

---

not.  
Conditions of restriction for the following entries should be considered:  
Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t

Volatile organic compounds : Directive 2004/42/EC  
VOC content in g/l: 702,1 g/l  
Product sub-category: Special finishes  
Coatings: All types  
VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 83,54 %, 702,1 g/l

### Other regulations:



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H351 : Suspected of causing cancer if inhaled.  
H372 : Causes damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.  
EUH071 : Corrosive to the respiratory tract.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Resp. Sens. : Respiratory sensitisation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
ES VLA	:	Spain. Environmental Limits for exposure to Chemical agents - Table 1: Occupational Exposure Values
ES VLB	:	Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure Values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
ES VLA / VLA-ED	:	Environmental Daily Limit Value
ES VLA / VLA-EC	:	Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## arecal Rust stop primer red/brown 400 ml

Version	Revision Date:	SDS Number:	Date of last issue: 25.06.2024
4.0	08.11.2024	9161531-00007	Date of first issue: 05.08.2021

---

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

ES / EN